

HSF RoHS

SPECIFICATIONS

Housing: Thermoplastic,UL94V-0 (PBT)
 Color: Black
 Contact:Copper Alloy
 Shell:Zinc Alloy
 Voltage Current Rating:1.0Amp.250V AC
 Insulation Resistance:500MΩ Min.
 Contact Resistance:35mΩ Max.
 Dielectric Withstanding Voltage:500V AC
 Temperature Range:-40°C to +105°C

No. of Pin	DIMENSIONS				
	A	B	C	D	E
50	52.55	46.37	30.48	39.57	34.35
68	64.00	57.77	41.91	51.00	45.78
100					

▲M2-56/M2.6

Ordering Information

6311-F XXX S D XX MNA OX

No.of Pins
50P,68P,100P

Connector Type
S=Straight

Contact Plating
G0:Gold Flash
S0:Gold Flash/Tin
S1:3U" ⌀

OPERATION

DRAW

YiYuSheng

17.11.23

SCALE

FIT

X.X ±0.30

CHECK

UNIT

mm

X.XX ±0.20

APPROVE

SIZE

A4

X.XXX ±0.10

ANGLE

SHEET

1/1

Angle ±3°

DIM

PROJ.

⌀

TOL

PART NO.

6311FXXXSDXXMNAOX

TITLE:

SCSI DB Female 180°

REV	DATE	MODIFICATION DESCRIPTION
A0	2017.11.23	NEW DRAWING

CHANGE

1

2

3

4

5

6

7

8

9